



Impulse® 1015 8 ohm - Black



OVERVIEW

Ultra-high performance from a weather-resistant, two-way (full-range or bi-ampable) speaker system that will provide up to 133 dB SPL. This system provides high power handling capability while maintaining a smooth, yet clear response. The elegant and durable trapezoidal enclosure is made of high-impact polypropylene with a metal grille. This system is comprised of a 15 inch Black Widow® woofer with a Kevlar® impregnated cone (with a specially treated surround) and a RX™ 22 two inch titanium compression driver coupled to a constant directivity horn with Sound Guard™ high frequency driver protection. Connections are made via two parallel 1/4 inch phone jacks for daisy-chaining and a switchable 4-pin Neutrik® Speakon® connector. This system will provide up to 133 dB SPL and can be used on the floor, speaker stand or be flown via top and bottom flying points.

FEATURES

- 2-way weather resistant enclosure with molded-in stand adapter and flying points on the top and bottom
- 1000 Watts program
- 2000 Watts peak
- One 15 inch Black Widow® woofer (1508-8 SPS BWX)
- RX™ 22 compression driver coupled with a molded-in 90 degree x 45 degree constant directivity horn
- Sound Guard™ high frequency driver protection circuit
- Available in black and white
- Response: 60 Hz to 18 kHz, +/- 3 dB
- Sensitivity: 100 dB SPL at 1W/1m
- Black available in 8 Ohms
- Cover available
- Weight Unpacked: 48.50 lb(22 kg)
- Weight Packed: 57.32 lb(26 kg)
- Width Packed: 24"(60.96 cm)
- Height Packed: 30"(76.2 cm)
- Depth Packed: 18.75"(47.625 cm)

