



PVH™ Series Bass Enclosures



Specifications

PVH™ 1516 -- Black carpet covering; Powdercoated black metal grille; Heavy duty high excursion 15" speaker; Two mid/high 8" speakers; 3-position eq switch; Ported cabinet; Spring loaded handles; Metal corners; Heavy duty hardware; Two combi input jacks; Rugged 15mm plywood construction; 900 watts program power handling.

Impedance: 8Ω

Power Handling (cont., prog., peak): 450W, 900W, 1800W

Sensitivity (1W/1m): 96dB

Frequency Response: 40Hz - 4.9KHz (sub mode = 40Hz - 370Hz)

Crossover Freq.: 300Hz

Weight: 74.0 lb / 33.5 Kg

Dimensions: W = 22.25" (56.5 cm), H = 29.75" (75.5 cm), D = 17.63" (44.7 cm)

PVH™ 212 -- Black carpet covering; Powdercoated black metal grille; High frequency horn tweeter with rotary L-pad attenuator; Two heavy duty 12" speakers; Ported cabinet; Metal corners; Heavy duty hardware; Two combi input jacks; Spring loaded handles; Rugged 15mm plywood construction; 900 watts program power handling.

Impedance: 8Ω

Power Handling (cont., prog., peak): 450W, 900W, 1800W

Sensitivity (1W/1m): 97dB

Frequency Response: 42Hz - 16KHz

Crossover Freq.: 2.8KHz

Weight: 76.5 lb / 34.7 Kg

Dimensions: W = 22.25" (56.5 cm), H = 29.75" (75.5 cm), D = 17.63" (44.7 cm)

PVH™ 410-- Black carpet covering; Powdercoated black metal grille; High frequency horn tweeter with rotary L-pad attenuator; Four heavy duty 10” speakers; Ported cabinet; Spring loaded handles; Metal corners; Heavy duty hardware; Two combi input jacks; Rugged 15mm plywood construction; 1,200 watts program power handling.

Impedance: 8Ω

Power Handling (cont., prog., peak): 600W, 1200W, 2400W

Sensitivity (1W/1m): 99dB

Frequency Response: 50Hz - 15KHz

Crossover Freq.: 3.5KHz

Weight: 83.0 lb / 37.6 Kg

Dimensions: W = 22.25” (56.5 cm), H = 29.75” (75.5 cm), D = 17.63” (44.7 cm)

PVH™ 210-- Black carpet covering; Powdercoated black metal grille; High frequency horn tweeter with rotary L-pad attenuator; Two heavy duty 12” speakers; Ported cabinet; Metal corners; Two combi input jacks; Rugged 15mm plywood Construction; Heavy duty hardware; 600 watts program power handling.

Impedance: 8Ω

Power Handling (cont., prog., peak): 300W, 600W, 1200W

Sensitivity (1W/1m): 95dB

Frequency Response: 45Hz - 15KHz

Crossover Freq.: 3.5KHz

Weight: 51.0 lb / 23.6 Kg

Dimensions: W = 22.25” (56.5 cm), H = 18.50” (47.0 cm), D = 17.63” (44.7 cm)



www.peavey.com

Warranty registration and information for U.S. customers available online at

www.peavey.com/warranty

or use the QR tag below



Features and specifications subject to change without notice.

Peavey Electronics Corporation 5022 Hartley Peavey Drive Meridian, MS 39305 (601) 483-5365 FAX (601) 486-1278



Logo referenced in Directive 2002/96/EC Annex IV
(OJ(L)37/38, 13.02.03 and defined in EN 50419: 2005
The bar is the symbol for marking of new waste and
is applied only to equipment manufactured after
13 August 2005